

The IBUC Advantage

All IBUCs are equipped with cutting-edge intelligent technology:

- Highest quality & exacting performance guaranteed through individual unit testing over temperature
- Superior linearity for maximum useable output power
- Amplifier overdrive protection
- User-selectable AGC/ALC for optimal performance & compatibility with modem adaptive coding
- New high capacity microprocessor & extended M&C functions
- Weatherized RJ45 Ethernet interface for simplified connection

ULTIMATE MANAGEMENT & CONTROL

- » Local Web Interface & NMS-Friendly SNMP «
- » 70+ User Configurable Thresholds & Alarms «
- » Upgraded Event Log with 1,000 Sensor Readings «
- » Performance Trend Analysis Tools & Statistical logs «
- » Embedded Web Pages for Universal Web Browser Access «

Applications

The **IBUC 2G** is a full-featured Intelligent Block Upconverter that now supports multicarrier transmission across the X-band spectrum and uses Gallium Nitride amplifier technology. GaN advantages include higher power in a smaller outdoor enclosure and low power consumption. Designed for long lifetime performance in demanding environments.

Multiple sensors & a new, high-capacity microprocessor provide tools to optimize remote terminal performance. The **IBUC 2G** is a perfect solution for mobile defense terminals operating in demanding environments.

Options

- 1+1 Transmit Redundancy with Eco-Mode
- High Stability Internal 10 MHz Reference with Auto-Detection
- Mounting Brackets
- N-Type, F-Type, or TNC Input Connectors
- Handheld Terminal
- Cyber Hardened Core M&C
- WGS (Wideband Global SATCOM) compatible
- External Waveguide Rx Reject Filter

X-Band IBUC 2G

100W Compact GaN IBUC For Multicarrier Application



New Cyber
Hardened
version
available

Multicarrier
Application

100W
P_{Lin} 50W

GaN
Tech
Amplifier

3
Year
Warranty

Note: Since not all the optional features can be combined, please, contact our sales team for further info at: Sales@Terrasatinc.com

X-Band 100W IBUC 2G - For Multicarrier Applications

| | | |
|--------------------------------|-------------------------------|--------------------------|
| Frequency Range | RF (MHz) | IF (MHz) |
| X-Band | 7900 to 8400 MHz | 950 to 1450 MHz |
| Input | | |
| VSWR/ Impedance | 1.5:1 / 50 Ohm | |
| Input Connector | Type N Female (50 Ohm) | |
| Input Connector Options | Type F (75 Ohm), TNC (50 Ohm) | |
| Input Power Detector | Standard Version ¹ | WGS Version ² |
| Range options: | -55 to -20 dBm | -35 to 0 dBm |

Gain

Small Signal Gain (L-band to RF) with attenuator set to 0 dB options:

| | | |
|--|-------------------------------|--------------------------|
| | Standard Version ¹ | WGS Version ² |
| | 81 dB min | 70 dB min |

¹Terrasats Standard Version has a higher gain to reduce the need for line amplifiers in long cable runs (IFL).
²WGS Compatible Versions have lower gain allowing operations to drive the IF signal up to 0 dBm.

| | | |
|--|--------------------------------|--|
| Attenuator Range | 30 dB variable in 0.1 dB steps | |
| Gain Flatness | | |
| Full Band | 3 dB p-p max | |
| 36 MHz | 1 dB p-p max | |
| 1 MHz | 0.25 dB p-p max | |
| Gain Variation Over Temperature | | |
| Open Loop | 3 dB p-p max | |
| With AGC | 1 dB p-p max | |

RF Output

| | |
|-----------|-----------|
| Interface | CPR-112G |
| VSWR | 1.3:1 max |

Output Power

| | |
|--------------------|---------|
| at P_{Sat} (typ) | +50 dBm |
| at P_{Lin} (min) | +47 dBm |

P_{Lin} is the maximum linear power as defined by MIL STD 188-164C
 Two-tone measured at 5MHz and 150 MHz spacing
 19 dB min of NPR (Noise Power Ratio) at +44 dBm.

| | |
|------------------------------------|-----------------------|
| Level stability with ALC | ± 0.5 dB |
| Output power detector range | Rated power to -20 dB |
| Power reading accuracy | ± 1.0 dB max. |

Spurious @ P_{Lin}

| | |
|-------------|--------------------------------|
| In Band | -65 dBc |
| Out of Band | Complies with MIL-STD 188-164C |

Harmonics @ P_{Lin}

| | |
|--|--------------|
| | -60 dBc max. |
|--|--------------|

Output Noise Power Density

| Transmit | Receive |
|------------------|--|
| Tx < - 76 dBm/Hz | Rx < - 76 dBm/Hz (Without Receive Reject Filter) |
| | Rx < - 166 dBm/Hz (With Optional Rx Reject Filter) |

| | |
|-------------------------|--------------------------|
| Mute | -70 dBc max |
| AM-PM Conversion | < 3.0 deg/dB @ P_{Lin} |

Group Delay

| | |
|-----------|---------------------------|
| Linear | 0.03 ns/MHz |
| Parabolic | 0.003 ns/MHz ² |
| Ripple | 1 ns p-p Over Any 36 MHz |

| | | |
|------------------------|--------------------|----------------|
| SSB Phase Noise | External Reference | IBUC 2G |
| 10 Hz | -115 dBc/Hz | -55 dBc/Hz |
| 100 Hz | -140 dBc/Hz | -80 dBc/Hz |
| 1 KHz | -150 dBc/Hz | -90 dBc/Hz |
| 10 KHz | -155 dBc/Hz | -95 dBc/Hz |
| 100 KHz | N/A | -100 dBc/Hz |
| 1 MHz | N/A | -110 dBc/Hz |

External Reference (Multiplexed on TX IFL)
Frequency: 10 MHz **Level:** -12 to +5 dBm
Internal Reference: Optional feature includes auto-detection of External Reference

Local Oscillator Frequency

| | |
|---------------|---------------|
| X-Band | 6950 MHz |
| Sense | Non-Inverting |

IBUC Power Supply

| | | | | |
|--------------------------|----|----------------|--|--------------------|
| Voltage | AC | 100 to 240 VAC | | 50 Hz / 60 Hz |
| Power Consumption | | P_{Lin} | | P_{Sat} |
| | | 100W | | 440 VA 520 VA |

Monitor & Control - For Standard Versions
 Ethernet (HTTP, Telnet, SNMPv2c) via RJ45 Connector
 RS232/485, Handheld Terminal via MS-Type Connector
 FSK multiplexed on TX IFL

Monitor & Control - For Cyber Hardened Versions
 Ethernet (HTTPS, SSHv2, SNMPv3 with USM and VACM) via RJ45 Connector
 RS232 via MS-Type Connector
 XSS (Cross Site Scripting)
 Two NTP Servers Providing Redundancy
 FIPS 140-2 compatible

The Cyber Hardened versions have embedded new high-end Cyber Security features, from hardware to software, including a new controller board and the new firmware. For further details, refer to the Cyber Hardened IBUCs' datasheet at www.terrasatinc.com/products/ or at the [Cyber Hardened webpage](https://www.terrasatinc.com/terrasat-communications-launches-new-cyber-hardened-intelligent-bucs/) on <https://www.terrasatinc.com/terrasat-communications-launches-new-cyber-hardened-intelligent-bucs/>

Environmental

| | |
|-----------------------|-------------------------|
| Operating Temperature | -40°C to +55°C |
| Relative Humidity | 100% Condensing |
| Altitude | 10,000 ft (3,000 m) ASL |

Mechanical

| | |
|--------|--|
| Size | 10.5 x 6 x 6.1 x in. 267 x 152 x 155 mm |
| Weight | 13.5 lbs 6.1 kg |

Specifications are subject to change without notice. Updated: October 10th 2023



Questions? Contact Us
 +1 (408) 782 5911
Sales@Terrasatinc.com

315 Digital Drive
 Morgan Hill, CA 95037
www.Terrasatinc.com