

## The IBUC Advantage

All IBUCs are equipped with cutting-edge intelligent technology:

- Highest quality & exacting performance guaranteed through individual unit testing over temperature
- Superior linearity for maximum useable output power
- Amplifier overdrive protection
- User-selectable AGC/ALC for optimal performance & compatibility with modem adaptive coding
- New high capacity microprocessor & extended M&C functions
- Weatherized RJ45 Ethernet interface for simplified connection

### ULTIMATE MANAGEMENT & CONTROL

- » Local Web Interface & NMS-Friendly SNMP «
- » 70+ User Configurable Thresholds & Alarms «
- » Upgraded Event Log with 1,000 Sensor Readings «
- » Performance Trend Analysis Tools & Statistical logs «
- » Embedded Web Pages for Universal Web Browser Access «

## Applications

The new **IBUC G** now supports multicarrier transmission across the full X-band spectrum. The **IBUC G** delivers the highest available output power, making it an ideal solution for high data rate multicarrier applications such as maritime, broadband, broadcast and network hubs.

Gallium Nitride amplifier technology enables smaller packaging for antenna mounting, eliminating the losses in long waveguide runs. And the greater power efficiency translates to an appreciable reduction in power consumption. Comparing favorably with earlier technology TWTAs, the GaN **IBUC G** delivers maximum linear output power with the reliability of solid state.

### Options

- 1+1 Transmit Redundancy with Eco-Mode
- High Stability Internal 10 MHz Reference with Auto-Detection
- Mounting Brackets
- N-Type or F-Type
- Handheld Terminal
- Cyber Hardened Core M&C
- WGS (Wideband Global SATCOM) compatible
- External Waveguide Rx Reject Filter

## X-Band IBUC G

200W GaN IBUC For Multicarrier Application



New Cyber  
Hardened  
version  
available

Multicarrier  
Application

200W  
P<sub>Lin</sub> 100W

GaN  
Tech  
Amplifier

3  
Year  
Warranty

**Note:** Since not all the optional features can be combined, please, contact our sales team for further info at: [Sales@Terrasatinc.com](mailto:Sales@Terrasatinc.com)

# X-Band 200W IBUC G - For Multicarrier Applications

<b>Frequency Range</b>	RF	IF
X-Band	7900 to 8400 MHz	950 to 1450 MHz
<b>Input</b>		
<b>VSWR/ Impedance</b>	1.5:1 / 50 Ohm	
<b>Input Connector</b>	Type N Female (50 Ohm)	
<b>Input Connector Options</b>	Type F (75 Ohm), TNC (50 Ohm)	
<b>Input Power Detector</b>	Standard Version <sup>1</sup>	WGS Version <sup>2</sup>
Range options:	-55 to -20 dBm	-35 to 0 dBm
<b>Gain</b>		
<b>Small Signal Gain</b> (L-band to RF) with attenuator set to 0 dB options:	Standard Version <sup>1</sup>	WGS Version <sup>2</sup>
	84 dB min	73 dB min
<sup>1</sup> Terrasats Standard Version has a higher gain to reduce the need for line amplifiers in long cable runs (IFL).		
<sup>2</sup> WGS Compatible Versions have lower gain allowing operations to drive the IF signal up to 0 dBm.		
<b>Attenuator Range</b>	30 dB variable in 0.1 dB steps	
<b>Gain Flatness</b>		
Full Band	3 dB p-p max	
36 MHz	1 dB p-p max	
1 MHz	0.25 dB p-p max	
<b>Gain Variation Over Temperature</b>		
Open Loop	3 dB p-p max	
With AGC	1 dB p-p max	
<b>RF Output</b>		
Interface	CPR-112G	
VSWR	1.3:1 max	
<b>Output Power</b>	200W	
at P <sub>Sat</sub> (typ)	+53 dBm	
at P <sub>Lin</sub> (min)	+50 dBm	
19 dB min of NPR (Noise Power Ratio) at:	+47 dBm	
P <sub>Lin</sub> is the maximum linear power as defined by MIL STD 188-164C		
Two-tone measured at 5MHz and 150 MHz spacing		
<b>Level stability with ALC</b>	± 0.5 dB	
<b>Output power detector range</b>	Rated power to -20 dB	
<b>Power reading accuracy</b>	± 1.0 dB max.	
<b>Spurious @P<sub>Lin</sub></b>		
In Band	-65 dBc	
Out of Band	Complies with MIL-STD 188-164C	
<b>Harmonics @ P<sub>Lin</sub></b>	-60 dBc max.	
<b>Output Noise Power Density</b>		
<b>Transmit</b>	<b>Receive</b>	
Tx < - 73 dBm/Hz	Rx < - 73 dBm/Hz (Without Receive Reject Filter)	
	Rx < - 163 dBm/Hz (With Optional Rx Reject Filter)	
<b>Mute</b>	-70 dBc max	
<b>AM-PM Conversion</b>	< 3.0 deg/dB @P <sub>Lin</sub>	
<b>Group Delay</b>		
Linear	0.03 ns/MHz	
Parabolic	0.003 ns/MHz <sup>2</sup>	
Ripple	1 ns p-p Over Any 36 MHz	

<b>SSB Phase Noise</b>	External Reference	<b>IBUC 2G</b>
10 Hz	-115 dBc/Hz	-55 dBc/Hz
100 Hz	-140 dBc/Hz	-80 dBc/Hz
1 KHz	-150 dBc/Hz	-90 dBc/Hz
10 KHz	-155 dBc/Hz	-95 dBc/Hz
100 KHz	N/A	-100 dBc/Hz
1 MHz	N/A	-110 dBc/Hz
<b>External Reference</b> (Multiplexed on TX IFL)		
<b>Frequency:</b> 10 MHz	<b>Level:</b> -12 to +5 dBm	
<b>Internal Reference:</b> Optional feature includes auto-detection of External Reference		
<b>Local Oscillator Frequency</b>		
<b>X-Band</b>	6950 MHz	
<b>Sense</b>	Non-Inverting	
<b>IBUC Power Supply</b>		
<b>Voltage</b>	AC 100 to 240 VAC	50 Hz / 60 Hz
<b>Power Consumption</b>	P <sub>Lin</sub>	P <sub>Sat</sub>
200W	800 VA	1000 VA
<b>Monitor &amp; Control - For Standard Versions</b>		
Ethernet (HTTP, Telnet, SNMPv2c) via RJ45 Connector		
RS232/485, Handheld Terminal via MS-Type Connector		
FSK multiplexed on TX IFL		
<b>Monitor &amp; Control - For Cyber Hardened Versions</b>		
Ethernet (HTTPS, SSHv2, SNMPv3 with USM and VACM) via RJ45 Connector		
RS232 via MS-Type Connector		
XSS (Cross Site Scripting)		
Two NTP Servers Providing Redundancy		
FIPS 140-2 compatible		
The Cyber Hardened versions have embedded new high-end Cyber Security features, from hardware to software, including a new controller board and the new firmware. For further details, refer to the Cyber Hardened IBUCs' datasheet at <a href="http://www.terrasatinc.com/products/">www.terrasatinc.com/products/</a> or at the <a href="https://www.terrasatinc.com/terrasat-communications-launches-new-cyber-hardened-intelligent-bucs/">Cyber Hardened webpage</a> on <a href="https://www.terrasatinc.com/terrasat-communications-launches-new-cyber-hardened-intelligent-bucs/">https://www.terrasatinc.com/terrasat-communications-launches-new-cyber-hardened-intelligent-bucs/</a>		
<b>Environmental</b>		
Operating Temperature	-40°C to +55°C	
Relative Humidity	100% Condensing	
Altitude	10,000 ft (3,000 m) ASL	
<b>Mechanical</b>		
<b>Weight</b>	33lbs 14.9 kg	
<b>Size</b>	16.2 x 10 x 7.6 in 411 x 254 x 193 mm	
(Dimensions not including isolators)		

Specifications are subject to change without notice.

Updated: June 6th 2024



**Questions? Contact Us**  
 +1 (408) 782 5911  
[Sales@Terrasatinc.com](mailto:Sales@Terrasatinc.com) or [Questions@Terrasatinc.com](mailto:Questions@Terrasatinc.com)

315 Digital Drive  
 Morgan Hill, CA 95037  
[www.Terrasatinc.com](http://www.Terrasatinc.com)